

HS-182-16BB

N型TOPCon

产品特性

N	B-O	0	≥25.2%	≥80%
1%				

182	*182	!0.25	,	247	!0.25	: -0.26%/
145±15						: +0.046%/
(+)	16*0.04!					



代							
	(%)	()	()	()	()	()	(%)
-182 -252	25.2	8.32	0.626	13.291	0.714	13.776	84.59
-182 -251	25.1	8.30	0.625	13.279	0.713	13.766	84.50
-182 -250	25.0	8.27	0.624	13.252	0.712	13.748	84.47
-182 -24	24.9	8.23	0.623	13.212	0.711	13.741	84.31
-182 -248	24.8	8.20	0.622	13.185	0.709	13.729	84.22
-182 -247	24.7	8.16	0.622	13.119	0.709	13.730	83.81
-182 -246	24.6	8.13	0.621	13.098	0.709	13.716	83.69
-182 -245	24.5	8.10	0.620	13.062	0.707	13.708	83.54
-182 -244	24.4	8.06	0.620	13.007	0.707	13.705	83.23
-182 -243	24.3	8.02	0.618	12.985	0.706	13.694	82.92
-182 -242	24.2	7.99	0.617	12.951	0.705	13.689	82.86
-182 -241	24.1	7.97	0.617	12.921	0.705	13.646	82.85
-182 -240	24.0	7.93	0.616	12.875	0.704	13.624	82.68
-182 -23	23.9	7.89	0.616	12.809	0.704	13.558	82.67
-182 -238	23.8	7.86	0.615	12.777	0.703	13.526	82.64
-182 -237	23.7	7.82	0.615	12.723	0.703	13.472	82.62
以上	: 1000 / ² , 1.5, 25°C 于 , 业						



代						
	(%)	()	()	()	()	()
-182 -20.5	> 20.5%	6.77	0.619	10.934	0.705	11.41
-182 -20.3	20.3%-20.5%	6.7	0.617	10.862	0.703	11.377
-182 -20.1	20.1%-20.3%	6.64	0.615	10.79	0.701	11.344
-182 -20.0	< 20.1%	6.6	0.614	10.754	0.7	11.323
以上	: 1000 / ² , 1.5, 25°C 于 , 业					